

AS5160™ & AS5160T™

Walk-Behind Scrubbers



*Exceptional Value
Floor Cleaning Equipment*

Simple. Rugged. Affordable.

AS5160™ & AS5160T™

Walk-Behind Scrubbers

STANDARD FEATURES:

SIMPLE

- Intuitive control panel with hour meter and battery capacity display
- Brush and pad driver can be un-installed automatically
- Speed reducing gear drive system of the traction drive version (AS5160T) ensures smooth operation with minimum effort

RUGGED

- Robust chassis system and roto-molded tanks, engineered to withstand heavy, daily use
- Heavy duty cast aluminum squeegee assembly for efficient water pick-up
- 5 year warranty; 8 year warranty on roto-mold components

AFFORDABLE

- 16 gallon tank and 20 inch cleaning path deliver maximum cleaning productivity
- Available with wet batteries or maintenance-free AGM batteries and onboard charger

TECHNICAL SPECIFICATIONS:

| AS5160™ & AS5160T™ SPECS | AS5160 | AS5160T |
|--------------------------------|---|---|
| Power | 850 W | 1,090 W |
| Dimensions (L x W x H) | 52 x 22 x 39 in (1,310 x 550 x 1,000 mm) | 52 x 22 x 39 in (1,310 x 550 x 1,000 mm) |
| Vacuum Motor Power | 350 W | 350 W |
| Traction Motor Power | – | 150 W |
| Brush Motor Power | 450 W | 450 W |
| Voltage | 24 V (2 x 12 V) | 24 V (2 x 12 V) |
| Noise Level | 69 ± 3 dB A | 69 ± 3 dB A |
| Cleaning Width | 20 inch (510 mm) | 20 inch (510 mm) |
| Maximum Working Efficiency | 23,680 ft ² /hr (2,200 m ² /hr) | 23,680 ft ² /hr (2,200 m ² /hr) |
| Solution / Recovery Tanks | 16 gal (61 L) | 16 gal (61 L) |
| Solution Flow (Min/Max) | 0 - 0.63 gal/min (0 - 2.4 L/min) | 0 - 0.63 gal/min (0 - 2.4 L/min) |
| Squeegee Width | 31 in (790 mm) | 31 in (790 mm) |
| Rear Wheels Diameter | 3 inch (2 pcs) | 3 inch (2 pcs) |
| Vacuum Suction | 47.2 in (1,200 mm H ₂ O) | 47.2 in (1,200 mm H ₂ O) |
| Brush Speed / Brush Pressure | 150 rpm / 60 lb (27 kg) | 150 rpm / 51 lb (23 kg) |
| Battery Options | 105 / 130 Ah wet; 105 Ah AGM | 105 / 130 Ah wet; 140 Ah AGM |
| Battery Compartment Dimensions | 14 x 14 x 12 in (350 x 350 x 300 mm) | 14 x 14 x 12 in (350 x 350 x 300 mm) |
| Run Time Per Charge | 2.5 hours | 2.5 hours |
| Onboard Charger | 10 A, 100 V~240 V | 10 A, 100 V~240 V |
| Shipping Weight | 254 lb (115 kg) | 271 lb (123 kg) |
| Climbability | 2% | 2% |
| Packaging Dimensions | 54 x 24 x 48 in (1,370 x 600 x 1,220 mm) | 54 x 24 x 48 in (1,370 x 600 x 1,220 mm) |

Specifications are subject to change without notice.



Manuals, parts, and videos
may be viewed online at
www.usviper.com

9435 Winnetka Avenue North • Brooklyn Park, MN 55445
Phone: 800.989.2235 • Fax: 800.989.6566

240 Superior Boulevard • Mississauga, Ontario, Canada L5T 2L2
Phone: 800.668.8400 • Fax: 800.263.5111

