AS530R

Mini ride-on scrubber dryer designed for large areas. An ideal choice for cleaning in hotels, bus and train stations, supermarkets, exhibition centers, shopping malls, schools and other institutions.

Benefits of AS530R Rider Scrubber

The AS530R is the first mini ride-on scrubber dryer in the user-friendly Viper series, known for providing high cleaning efficiency at attractive prices. With battery and tank capacity to clean for hours, this machine is ready to take on areas of more than 5.000 m2.

- An integrated on-board charger enables easy plug-in and battery charge at any outlet
- Water solution level indicator with volume visible on the tank
- Large opening to the 73 liter recovery tank allows easy cleaning
- Built-in squeegee hanging system on recovery tank for easy machine transfer in narrow areas
- Productivity: Working width 53 cm, Squeegee width 73 cm
- Versatility: Cleans tiled floors, vinyl, sealed wood, marble, concrete and other surfaces
- Efficiency: Speed 5.5 km/h, Climb rate 10%
- High performance: Brush pressure 23 kg, Brush speed 160 rpm
- Low sound level: 69 dB(A) enabling daytime cleaning
- Robust design: Front bumper, strong main frame and heavy-duty aluminum squeegee
- User-friendly dashboard: Intuitive display and buttons
- Standard equipment

	Standard equipment							
	Included accessories	Ref. no.	Min. required	AS530R-US RIDE ON SCRUBBER 24V	AS530R-US RIDER 130AH WET	AS530R-US RIDER 140AH AGM		
Brush	Brush							
0	KIT BRUSH	VR25014	0					
Pad Holder		1			1			
(PAD DRIVER 20	VR25022	0	•				
Disc Brush 5	30 mm							
0	AS530R CLEAN GRIT BRUSH 0.9 MM	VR25049	0	•				
Squeegee, B	Squeegee, Blade, Skirt and Splash Guard							
	NEOPRENE 17 IN BLADE FRONT	VF90103	0	•				





Picture shown may not represent model quoted

All information provided in this document is subject to change without prior notice

	Included accessories	Ref. no.	Min. required	AS530R-US RIDE ON SCRUBBER 24V	AS530R-US RIDER 130AH WET	AS530R-US RIDER 140AH AGM
	NEOPRENE 17 IN BLADE REAR	VF90104	0	•		
e	SQUEEGEE ASSEMBLY	VR26000	0			

• Standard equipment

	Included accessories	Ref. no.	Min. required	AS530R W130 PKG	AS530R A140 PKG	AS530R MEX COMPLETE
Brush			required	TRO	110	
0	KIT BRUSH	VR25014	0			
Pad Holder						
(PAD DRIVER 20	VR25022	0	•	•	•
Disc Brush 53	30 mm					
0	AS530R CLEAN GRIT BRUSH 0.9 MM	VR25049	0	•	•	•
Squeegee, B	ade, Skirt and Splash Guard	1				
	NEOPRENE 17 IN BLADE FRONT	VF90103	0	•	•	•
	NEOPRENE 17 IN BLADE REAR	VF90104	0	•	•	•
•	SQUEEGEE ASSEMBLY	VR26000	0			



Ref. no.500004715638507256385073PRODUCT FEATURESDisc brush version•Battery version•Compact design•Recovery emplying hotes•On-board charger•Water level indicator•ModelAS530R W130 PKGAS530R A140 PKGAS530R M160 PKGRef. no.AS530R M130 PKGAS530R A140 PKGAS530R M160 PKGRef. no.AS530R M130 PKGAS530R A140 PKGAS530R M160 PKGPRODUCT FEATURES•••Disc brush version•••Battery version•••Compact design•••Recovery emplying hoses•••Recovery emplying hoses•••Recovery emplying hoses•••Technical specifications0.6••Technical specifications0.6••View motor hp (W)0.6 hp••View motor hp (W)0.5 hp••Soution flow rate gom (timin)0.22-0.5 gall••Soution flow rate gom (timin)0.22-0.5 gall• </th <th>Model</th> <th>AS530R-US RIDE ON SCRUBBER 24V</th> <th>AS530R-US RIDER 130AH WET</th> <th>AS530R-US RIDER 140AH AGM</th>	Model	AS530R-US RIDE ON SCRUBBER 24V	AS530R-US RIDER 130AH WET	AS530R-US RIDER 140AH AGM
Disc brush versionImage: constraint of the second seco	Ref. no.	50000417	56385072	56385073
Battery version•Compact design•Recovery emplying hoses•On-board charger•Water level indicator•ModelAsson Wator JoeAsson Attaor JoeRef. no.Asson Stator Joe50000417MEXPRODUCT FEATURES••Disc brush version••Battery version••Compact design••Recovery emplying hoses••On-board charger••Vater level indicator••On-board design••Recovery emplying hoses••On-board charger••Yater level indicator••Nater level indicator••On-board charger••Nater level indicator••Technical specifications••Technical specifications••Stath motor (W)••On-board (MHZO)••Vacuum (MHZO)••Sound pressure level (BfA)••Orductivity rate fifthr (MFHR)••Sound pressure level (BfA)••On-board (MMZO)••Sound pressure level (BfA)••Sound pressure level	PRODUCT FEATURES			
Compact design•Recovery emplying hoses•On-board charger•Wate level indicator•Ref. no.Asson RVI30 PKAsson RA140 PKComPact RefRef. no.Asson RVI30 PKAsson RA140 PKComPact RefRecovery emplying hoses00.000417MEX•Dic brush version•••Compact design0•••Recovery emplying hoses••••On-board charger••••No-board charger• <td>Disc brush version</td> <td>•</td> <td></td> <td></td>	Disc brush version	•		
Recovery emptying hoses.On-board charger.Water level indicator.ModelASS30R WI3D PKASS30R AI4D PKASS30R MEXRef. no.ASS30R MI2D PKDisc Druct FEATURESDisc Druct versionBattery versionCompact designOn-board chargerVater level indicatorTechnical specificationsDischards specificationsStatury versionCompact designNoncork programNater level indicatorVater level indicatorStatury versionConspact designNator (M)Vater level indicatorVater level indicatorStatury specificationsStatury specificationsStatury specificationsStatury specificationsStatury specificationsStatury specificationsStatury specificationsStatury specifications	Battery version	•		
On-board charger Water level indicator.ModelASS30R WI30 PKASS30R AL40 PKASS30R MEXRef. no.ASS30R NI30 PKASS30R AL40 PKSS30R MEXRef. no.ASS30R NI30 PKASS30R AL40 PKSS30R MEXPRODUCT FEATURESDisc brash versionCompact designRecovery emplying hosesOn-board chargerVater level indicatorTechnical specificationsBittery versionCompact designOn-board chargerWater level indicatorTechnical specificationsBittery typeYoacum motor power (W)Yoacum (MM12Q)Bittery typeYoacum (MM2Q)Yoacum (MM1Q)Yoacum (MM1Q)Yoacum (MM1Q)Yoacum (MM1Q)Yoacum (MM1Q)Yoacum (MM1Q)Yoacum (MM1Q)Yoacum (MM1Q)<	Compact design	•		
Water level indicator•ModelAss30R W130 PKGAss30R A140 PKGAss30R MEX COMPLETERef. no.Ass30R 130 PKGAss30R A140 PKG600004 17/MEXPRODUCT FEATURES•••Disc brush version•••Battery version•••Compact design•••Recovery emptying hoses•••On-baard charger•••Vater level indicator•••Technical specifications0.41p**Drive motor hp (W)0.41p**Vacuum motor power (W)0.51p**Vacuum motor power (W)0.51p**Solution flow rate gpm (Imin)0.220-53gall**Solution flow rate gpm (Imin)0.220-53gall**Solution rate (%)10%10%**Solution rate (%)10%10%** <td>Recovery emptying hoses</td> <td>•</td> <td></td> <td></td>	Recovery emptying hoses	•		
Model ASS30R W130 PKG ASS30R A140 PKG ASS30R MEXC Ref. no. ASS30R W130 PKG ASS30R A140 PKG S0000417/MEX PRODUCT FEATURES Disc brush version Battery version Compact design Recovery emptying hoses On-board charger Wate level indicator Technical specifications O.6.0p 1040AH AGM Drive motor hp (W) O.6hp 140AH AGM Souun motor power (W) O.5hp 140AH AGM Souun forkers level (dB(A)) 669 Souun forker ster (W) 0.5hp Souun forker ster (MMH2O) 48in Souun forker ster (MMH2O) 680 Souun motor power (W) 0.5hp Souun fow ra	On-board charger	•		
Nuclei ASSOR WISD PKS ASSOR A TAD PKS COMPLETE Ref. no. ASSOR A TAD PKS \$5000417MEX PRODUCT FEATURES • • Disc brush version • • Battery version • • Compact design • • Recovery emptying hoses • • On-board charger • • Water level indicator • • Technical specifications ASSOR-US RIPER 24V * • Drive motor hp (W) 0.6hp * * * Battery type 245a/h AGM * * * * Vacuum motor power (W) 0.5hp *<	Water level indicator	•		
Appropriate and the service of the service	Model	AS530R W130 PKG	AS530R A140 PKG	
Disc brush version•••Battery version••••Compact design••••Recovery emptying hoses••••On-board charger••••Water level indicator••••Technical specificationsASS30R-US RIDER 140AH AGMASS30R-US RIDER 140AH AGMASS30R-US RIDER 140AH AGMDrive motor hp (W)0.6hp•••Vacuum motor power (W)0.5hp•••Battery type245a/h AGM•••Yoduum (MMH2O)69••••Solution flow rate gpm (/min.)0.22-0.53gall•••Cleaning width (MM)20in174•••Min. aisle turn (cm)11%19gal•••Asciumbing rate (%)19%19gal•••Solution tank (L)19gal••••Fort wheel dimensions (cm)6.8in••••	Ref. no.	AS530R130PKGC	AS530RAGMPKGC	50000417MEX
Battery versionCompact designRecovery emptying hosesOn-board chargerWater level indicatorTechnical specificationsASS30R-US RIDE 24VASS30R-US RIDE 130AH WETASS30R-US RIDE 140AH AGMDrive motor hp (W)0.4hpBrush motor (W)0.6hpVacuum motor power (W)0.5hpBattery type245a/h AGMYou (MMH2O)Sound pressure level (dB(A))Productivity rate ff'/hr (M*/HR)Cleaning width (MM)Max climbing rate (%)Solution tank (L)Recovery tank (L)Fort wheel dimensions (cm)6.8in	PRODUCT FEATURES			
Compact design••Recovery emptying hoses•••On-board charger•••Water level indicator•••Technical specificationsASS30R-US RIDE ON SCRUBBER 24VASS30R-US RIDE 130AH WETASS30R-US RIDE 140AH AGMDrive motor hp (W)0.4hp••Brush motor (W)0.6hp••Vacuum motor power (W)0.5hp••Battery type245a/h AGM••Youcu (MMH2O)69••Sound pressure level (dB(A))0.22-0.53gall•Cleaning width (MM)0.22-0.53gall••Cleaning width (MM)10%••Solution flow rate gpm (Imin.)0.22-0.53gall•Cleaning rate (%)10%••Solution tank (L)19gal••Recovery tank (L)19.2gal••Fort wheel dimensions (cm)6.8in••	Disc brush version	•	•	•
Recovery emptying hosesOn-board chargerWater level indicatorTechnical specificationsSSSSOR-US RIDER 24VASSSOR-US RIDER 130AH WETASSSOR-US RIDER 140AH AGMDrive motor hp (W)0.4hp.Brush motor (W)0.6hp.Vacuum motor power (W)0.5hp.Battery type245a/h AGM.Vacuum (MMH2O)48in.Sound pressure level (dB(A))69.Productivity rate ft ² /hr (M ² /HR)2650.Solution flow rate gpm (//min.)0.22-0.53gall.Cleaning width (MM)20in.Min. aisle turn (cm)114Max climbing rate (%)10%Solution tank (L)19galRecovery tank (L)6.8in	Battery version	•	•	•
On-board charger•••Water level indicator••••Technical specificationsAS30R-US RIDER ON SCRUBBER 24VAS30R-US RIDER 130AH WETAS30R-US RIDER 140AH AGMDrive motor hp (W)0.4hp0.4hpBrush motor (W)0.6hp0.5hpVacuum motor power (W)0.5hp5Battery type245a/h AGMVacuum (MH2O)48inSound pressure level (dB(A))69Productivity rate ff/hr (M*/HR)2650Solution flow rate gam (/min.)0.22-0.53gallCleaning width (MM)20inMin. aise turn (cm)174Max climbing rate (%)10%Solution tank (L)19galFecovery tank (L)19.2galFront wheel dimensions (cm)6.8in	Compact design	•	•	•
Water level indicator••Pechnical specificationsAss30R-US RIDER 24VAss30R-US RIDER 130AH WETAss30R-US RIDER 140AH AGMDrive motor hp (W)0.4hp0.4hpBrush motor (W)0.6hp0.5hpVacuum motor power (W)0.5hp48inVacuum (MMH2O)48in-Sound pressure level (dB(A))69-Productivity rate ft?/hr (M?/HR)0.2c-0.53gall-Cleaning width (MM)0.2l-0.53gall-Cleaning width (MM)174Max climbing rate (%)10%Solution tank (L)19galRecovery tank (L)19.2galFront wheel dimensions (cm)6.8in	Recovery emptying hoses	•	•	•
Technical specificationsAssage US RUDER ON SCRUBBER 24VAssage US RUDER 130AH WETAssage US RUDER 140AH ASMDrive motor hp (W)0.4hpBrush motor (W)0.6hpVacuum motor power (W)0.5hpBattery type245a/h AGMVacuum (MMH2O)48inSound pressure level (dB(A))69Productivity rate ft ¹ /hr (M ² /HR)2650Solution flow rate gpm (l/min.)0.22-0.53gallCleaning width (MM)20inMin. aisle turn (cm)1174Max climbing rate (%)10%Solution tank (L)19galRecovery tank (L)19.2galFront wheel dimensions (cm)6.8in				
Technical specificationsON SCRUBBER 24VA3300-05 RIDEX A3300-05 RIDEX A3000-05 RID	On-board charger	•	•	•
Brush motor (W)0.6hpVacuum motor power (W)0.5hpBattery type245a/h AGMVacuum (MMH2O)48inSound pressure level (dB(A))69Productivity rate ft²/hr (M²/HR)2650Solution flow rate gpm (//mi.)0.22-0.53gallCleaning width (MM)20inMin. aisle turn (cm)174Max climbing rate (%)10%Solution tank (L)19galFront wheel dimensions (cm)6.8in		•	•	•
Vacuum motor power (W)0.5hpBattery type245a/h AGMVacuum (MMH2O)48inSound pressure level (dB(A))69Productivity rate ft²/hr (M²/HR)2650Solution flow rate gpm (l/min.)0.22-0.53gallCleaning width (MM)20inMin. aisle turn (cm)174Max climbing rate (%)10%Solution tank (L)19galRecovery tank (L)19.2galFront wheel dimensions (cm)6.8in	Water level indicator	ON SCRUBBER		
Battery type245a/h AGMVacuum (MMH2O)48inSound pressure level (dB(A))69Productivity rate ft²/hr (M²/HR)2650Solution flow rate gpm (l/min.)0.22-0.53gallCleaning width (MM)20inMin. aisle turn (cm)174Max climbing rate (%)10%Solution tank (L)19galRecovery tank (L)19.2galFront wheel dimensions (cm)6.8in	Water level indicator Technical specifications	ON SCRUBBER 24V		
Vacuum (MMH2O)48inSound pressure level (dB(A))69Productivity rate ft²/hr (M²/HR)2650Solution flow rate gpm (l/min.)0.22-0.53gallCleaning width (MM)20inMin. aisle turn (cm)174Max climbing rate (%)10%Solution tank (L)19galRecovery tank (L)19.2galFront wheel dimensions (cm)6.8in	Water level indicator Technical specifications Drive motor hp (W)	ON SCRUBBER 24V 0.4hp		
Sound pressure level (dB(A))69Productivity rate ft²/hr (M²/HR)2650Solution flow rate gpm (l/min.)0.22-0.53gallCleaning width (MM)20inMin. aisle turn (cm)174Max climbing rate (%)10%Solution tank (L)19galRecovery tank (L)19.2galFront wheel dimensions (cm)6.8in	Water level indicator Technical specifications Drive motor hp (W) Brush motor (W)	ON SCRUBBER 24V 0.4hp 0.6hp		
Productivity rate ft²/hr (M²/HR)2650Solution flow rate gpm (l/min.)0.22-0.53gallCleaning width (MM)20inMin. aisle turn (cm)174Max climbing rate (%)10%Solution tank (L)19galRecovery tank (L)19.2galFront wheel dimensions (cm)6.8in	Water level indicator Technical specifications Drive motor hp (W) Brush motor (W) Vacuum motor power (W)	ON SCRUBBER 24V 0.4hp 0.6hp 0.5hp		
Solution flow rate gpm (l/min.)0.22-0.53gallCleaning width (MM)20inMin. aisle turn (cm)174Max climbing rate (%)10%Solution tank (L)19galRecovery tank (L)19.2galFront wheel dimensions (cm)6.8in	Water level indicator Technical specifications Drive motor hp (W) Brush motor (W) Vacuum motor power (W) Battery type	ON SCRUBBER 24V 0.4hp 0.6hp 0.5hp 245a/h AGM		
Cleaning width (MM)20inMin. aisle turn (cm)174Max climbing rate (%)10%Solution tank (L)19galRecovery tank (L)19.2galFront wheel dimensions (cm)6.8in	Water level indicator Technical specifications Drive motor hp (W) Brush motor (W) Vacuum motor power (W) Battery type Vacuum (MMH2O)	ON SCRUBBER 24V 0.4hp 0.6hp 0.5hp 245a/h AGM 48in		
Min. aisle turn (cm)174Max climbing rate (%)10%Solution tank (L)19galRecovery tank (L)19.2galFront wheel dimensions (cm)6.8in	Water level indicator Technical specifications Drive motor hp (W) Brush motor (W) Vacuum motor power (W) Battery type Vacuum (MMH2O) Sound pressure level (dB(A))	ON SCRUBBER 24V 0.4hp 0.6hp 0.5hp 245a/h AGM 48in 69		
Max climbing rate (%)10%Solution tank (L)19galRecovery tank (L)19.2galFront wheel dimensions (cm)6.8in	Water level indicatorTechnical specificationsDrive motor hp (W)Brush motor (W)Vacuum motor power (W)Battery typeVacuum (MMH2O)Sound pressure level (dB(A))Productivity rate ft²/hr (M²/HR)	ON SCRUBBER 24V 0.4hp 0.6hp 0.5hp 245a/h AGM 48in 69 2650		
Solution tank (L)19galRecovery tank (L)19.2galFront wheel dimensions (cm)6.8in	Water level indicator Technical specifications Drive motor hp (W) Brush motor (W) Vacuum motor power (W) Battery type Vacuum (MMH2O) Sound pressure level (dB(A)) Productivity rate ft²/hr (M²/HR) Solution flow rate gpm (l/min.)	ON SCRUBBER 24V 0.4hp 0.6hp 0.5hp 245a/h AGM 48in 69 2650 0.22-0.53gall		
Recovery tank (L)19.2galFront wheel dimensions (cm)6.8in	Water level indicator Technical specifications Drive motor hp (W) Brush motor (W) Vacuum motor power (W) Battery type Vacuum (MMH2O) Sound pressure level (dB(A)) Productivity rate ft²/hr (M²/HR) Solution flow rate gpm (l/min.) Cleaning width (MM)	ON SCRUBBER 24V 0.4hp 0.6hp 0.5hp 245a/h AGM 48in 69 2650 0.22-0.53gall 20in		
Front wheel dimensions (cm) 6.8in	Water level indicatorTechnical specificationsDrive motor hp (W)Brush motor (W)Vacuum motor power (W)Battery typeVacuum (MMH2O)Sound pressure level (dB(A))Productivity rate ft²/hr (M²/HR)Solution flow rate gpm (I/min.)Cleaning width (MM)Min. aisle turn (cm)	ON SCRUBBER 24V 0.4hp 0.6hp 0.5hp 245a/h AGM 48in 69 2650 0.22-0.53gall 20in 174		
	Water level indicatorTechnical specificationsDrive motor hp (W)Brush motor (W)Vacuum motor power (W)Battery typeVacuum (MMH2O)Sound pressure level (dB(A))Productivity rate ft²/hr (M²/HR)Solution flow rate gpm (l/min.)Cleaning width (MM)Min. aisle turn (cm)Max climbing rate (%)	ON SCRUBBER 24V 0.4hp 0.6hp 0.5hp 245a/h AGM 48in 69 2650 0.22-0.53gall 20in 174 10%		
Rear wheel dim (cm) / type 9in	Water level indicatorFechnical specificationsDrive motor hp (W)Brush motor (W)Vacuum motor power (W)Battery typeVacuum (MMH2O)Sound pressure level (dB(A))Productivity rate ft²/hr (M²/HR)Solution flow rate gpm (I/min.)Cleaning width (MM)Min. aisle turn (cm)Max climbing rate (%)Solution tank (L)	ON SCRUBBER 24V 0.4hp 0.6hp 0.5hp 245a/h AGM 48in 69 2650 0.22-0.53gall 20in 174 10% 19gal		
	Water level indicatorFechnical specificationsDrive motor hp (W)Brush motor (W)Vacuum motor power (W)Battery typeVacuum (MMH2O)Sound pressure level (dB(A))Productivity rate ft²/hr (M²/HR)Solution flow rate gpm (I/min.)Cleaning width (MM)Min. aisle turn (cm)Max climbing rate (%)Solution tank (L)Recovery tank (L)	ON SCRUBBER 24V 0.4hp 0.6hp 0.5hp 245a/h AGM 48in 69 2650 0.22-0.53gall 20in 174 10% 19gal 19.2gal		



Technical specifications	AS530R-US RIDE ON SCRUBBER 24V	AS530R-US RIDER 130AH WET	AS530R-US RIDER 140AH AGM
Squeegee width (MM)	30in		
Brush diameter (MM)	20in		
Brush speed (RPM)	160		
Length x width x height (MM)	53.5x23x44in		
Battery compartment size (LXWXH) (MM)	13.8x15x11.8in		
Net weight (KG)	308lbs		
Shipping weight (KG)	540lbs		
Charging system			
Max. speed	3.4m/hr		
Packaging dimensions	58x28x51in		
Technical specifications	AS530R W130 PKG	AS530R A140 PKG	AS530R MEX COMPLETE
Drive motor hp (W)	0.4hp	0.4hp	0.4hp
Brush motor (W)	0.6hp	0.6hp	0.6hp
Vacuum motor power (W)	0.5hp	0.5hp	0.5hp
Battery type	245a/h AGM	245a/h AGM	245a/h AGM
Vacuum (MMH2O)	48in	48in	48in
Sound pressure level (dB(A))	69	69	69
Productivity rate ft²/hr (M²/HR)	2650	2650	2650
Solution flow rate gpm (I/min.)	0.22-0.53gall	0.22-0.53gall	0.22-0.53gall
Cleaning width (MM)	20in	20in	20in
Min. aisle turn (cm)	174	174	174
Max climbing rate (%)	10%	10%	10%
Solution tank (L)	19gal	19gal	19gal
Recovery tank (L)	19.2gal	19.2gal	19.2gal
Front wheel dimensions (cm)	6.8in	6.8in	6.8in
Rear wheel dim (cm) / type	9in	9in	9in
Squeegee width (MM)	30in	30in	30in
Brush diameter (MM)	20in	20in	20in
Brush speed (RPM)	160	160	160
Length x width x height (MM)	53.5x23x44in	53.5x23x44in	53.5x23x44in
Battery compartment size (LXWXH) (MM)	13.8x15x11.8in	13.8x15x11.8in	13.8x15x11.8in
Net weight (KG)	308lbs	308lbs	308lbs
Shipping weight (KG)	540lbs	540lbs	540lbs
Charging system			
Max. speed	3.4m/hr	3.4m/hr	3.4m/hr
Packaging dimensions	58x28x51in	58x28x51in	58x28x51in



All information provided in this document is subject to change without prior notice

ullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	AS530R-US RIDE ON SCRUBBER 24V	AS530R-US RIDER 130AH WET	AS530R-US RIDER 140AH AGM
Brush						
0	KIT BRUSH	VR25014	0	0		
Pad Holder						
	PAD DRIVER 20	VR25022	0	•		
Squeegee, Bla	ade, Skirt and Splash Guard					
	17 BLADE FRONT PU	VF90146	0	0		
	17 BLADE REAR PU	VF90147	0	0		
	NEOPRENE 17 IN BLADE FRONT	VF90103	0	•		
	NEOPRENE 17 IN BLADE REAR	VF90104	0	•		
\smile	SKIRT KIT LEFT AS530R	VR25026	0	0		
\smile	SKIRT KIT RIGHT AS530R	VR25025	0	0		
0	SQUEEGEE ASSEMBLY	VR26000	0	0		
Viper Accesso	bry					
	KIT WARNING LIGHT	VR17160	0			
Squeegee Bla	de					



	Accessories	Ref. no.	Min. required	AS530R-US RIDE ON SCRUBBER 24V	AS530R-US RIDER 130AH WET	AS530R-US RIDER 140AH AGM
	SQUEEGEE BLADE FRONT- LINATEX	VR26023	0	0		
	SQUEEGEE BLADE REAR-LINATEX	VR26024	0	0		
Disc Brush 53	30 mm					
0	AS530R CLEAN GRIT BRUSH 0.9 MM	VR25049	0	٠		

ullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	AS530R W130 PKG	AS530R A140 PKG	AS530R MEX COMPLETE
Brush						
	KIT BRUSH	VR25014	0	0	0	0
Pad Holder						
(PAD DRIVER 20	VR25022	0	•	•	•
Squeegee, B	ade, Skirt and Splash Guard					
	17 BLADE FRONT PU	VF90146	0	0	0	0
	17 BLADE REAR PU	VF90147	0	0	0	0
	NEOPRENE 17 IN BLADE FRONT	VF90103	0	•	•	•
	NEOPRENE 17 IN BLADE REAR	VF90104	0	•	•	•



	Accessories	Ref. no.	Min. required	AS530R W130 PKG	AS530R A140 PKG	AS530R MEX COMPLETE
\smile	SKIRT KIT LEFT AS530R	VR25026	0	0	0	0
\smile	SKIRT KIT RIGHT AS530R	VR25025	0	0	0	0
	SQUEEGEE ASSEMBLY	VR26000	0	0	0	0
Viper Access	ory					
	KIT WARNING LIGHT	VR17160	0			
Squeegee Bla	ade					
	SQUEEGEE BLADE FRONT- LINATEX	VR26023	0	0	0	0
	SQUEEGEE BLADE REAR-LINATEX	VR26024	0	0	0	0
Disc Brush 53	Disc Brush 530 mm					
0	AS530R CLEAN GRIT BRUSH 0.9 MM	VR25049	0	•	•	•

